



Specification sheet

Part No. GA5348-01

2-40-9.5-20 SLIP RING

Published 06.02.23

Part No. GA5348-01

2-40-9.5-20 SLIP RING



Number of Rings 2

Outer Diameter (mm) 40

Max Amp Rating No Test Data Approx 30

Ring width (mm) 9.5

Bore (mm) 20

Min Voltage Spacing mm 3

Specifications

Part No. GA5348-01

2-40-9.5-20 SLIP RING



MATERIAL properties

Property	Value	Standard
RING MATERIAL	PB1	-
RISER MATERIAL	COPPER (C101)	-
INSULATION MATERIAL	DMC	-
HUB MATERIAL	N/A	-
RING PLATING MATERIAL	N/A	-

RISERS properties

Property	Value	Standard
TYPE	FLAT	-
LENGTH (mm)	10	-
WIDTH (mm)	5	-
THICKNESS (mm)	1	-
THREAD SIZE (mm)	N/A	-
RISER PLATING MATERIAL	N/A	-
NUMBER OF RISERS	2	-

TERMINALS properties

Property	Value	Standard
	N/A	-

Part No. GA5348-01

2-40-9.5-20 SLIP RING



GENERAL INFORMATION properties

Property	Value	Standard
OVERALL LENGTH (mm)	36.5	-
SECURING METHOD - THREAD SIZE	N/A	-
SECURING METHOD - NUMBER OF HOLES	N/A	-
KEY WAY (Y/N)	N	-
BORE SIZE	20	-

ELECTRICAL INFORMATION properties

Property	Value	Standard
VOLTAGE RATING MAX		-
CURRENT RATING MAX	20A	-



Part No. GA5348-01

2-40-9.5-20 SLIP RING

BGB (UK)

Call us today on +44 (0) 1476 576280

Dysart Road
Grantham
Lincolnshire
NG31 7NB

BGB (USA)

Call us today on +1 804 451 5211

1060 Port Walthall Drive
Colonial Heights
VA 23834
USA

www.bgbinnovation.com