



Specification sheet

Part No. GA5352-01

2-60-10-25 M6 SLIPRING

Published 06.02.23

Part No. GA5352-01

2-60-10-25 M6 SLIPRING



Number of Rings 2

Outer Diameter (mm) 60

Max Amp Rating No Test Data Approx 65

Ring width (mm) 10

Bore (mm) 25

Min Voltage Spacing mm 7

Specifications

Part No. GA5352-01

2-60-10-25 M6 SLIPRING



MATERIAL properties

Property	Value	Standard
RISER MATERIAL	BRONZE PB1	-
INSULATION MATERIAL	Cu ALLOY	-
HUB MATERIAL	DMC	-
RING PLATING MATERIAL	N/A	-

RISERS properties

Property	Value	Standard
TYPE	N/A	-
LENGTH (mm)	FLAT	-
WIDTH (mm)	15	-
THICKNESS (mm)	N/A	-
THREAD SIZE (mm)	N/A	-
RISER PLATING MATERIAL	M6	-
NUMBER OF RISERS	N/A	-

TERMINALS properties

Property	Value	Standard
TYPE	2	-
BLADE TERMINAL SIZE	M6	-

Part No. GA5352-01

2-60-10-25 M6 SLIPRING



GENERAL INFORMATION properties

Property	Value	Standard
OVERALL LENGTH (mm)	N/A	-
SECURING METHOD - THREAD SIZE	59mm	-
SECURING METHOD - NUMBER OF HOLES	M5	-
KEY WAY (Y/N)	2	-
BORE SIZE	N	-

ELECTRICAL INFORMATION properties

Property	Value	Standard
VOLTAGE RATING MAX	Ø25 (H7)	-
CURRENT RATING MAX	7mm 50v NEEDS CONFIRMING* less than 3mm across surface	-



Part No. GA5352-01

2-60-10-25 M6 SLIPRING

BGB (UK)

Call us today on +44 (0) 1476 576280

Dysart Road
Grantham
Lincolnshire
NG31 7NB

BGB (USA)

Call us today on +1 804 451 5211

1060 Port Walthall Drive
Colonial Heights
VA 23834
USA

www.bgbinnovation.com