



Specification sheet

Part No. GA5439

2-45-10-24 SLIPRING

Print Date 27.07.23

Part No. GA5439

2-45-10-24 SLIPRING



Number of Rings 2
Outer Diameter (mm) 45
Max Amp Rating No Test Data Approx 20

Ring width (mm) 10
Bore (mm) 24
Min Voltage Spacing mm 3

Specifications

TERMINALS properties

Property	Value	Standard
BLADE TERMINAL SIZE	BRONZE PB1	-

Part No. GA5439

2-45-10-24 SLIPRING



General Information properties

Property	Value	Standard
OVERALL LENGTH LENGTH (mm)	Cu ALLOY	-
SECURING METHOD - THREAD SIZE	DMC	-
SECURING METHOD - NUMBER OF HOLES	N/A	-
KEY WAY (Y/N)	N/A	-
BORE SIZE	FLAT	-
Force	50v NEEDS CONFIRMING* 60439-1	-

ELECTRICAL INFORMATION properties

Property	Value	Standard
VOLTAGE RATING MAX	12	-
CURRENT RATING MAX	5	-

properties

Property	Value	Standard
	1	-
	21A	-

Part No. GA5439

2-45-10-24 SLIPRING



Material properties

Property	Value	Standard
Holder Material	N/A	-
Brush Material	N/A	-
Plating Material	2	-
Conductor Material	N/A	-
Braid Material	N/A	-
Spring Material	37	-

Termination properties

Property	Value	Standard
Type	N/A	-
Size (mm)	N/A	-
Thread Size	N	-

Current properties

Property	Value	Standard
Max Amps	Ø24 (H7)	-



Part No. GA5439

2-45-10-24 SLIPRING

BGB (UK)

Call us today on +44 (0) 1476 576280

Dysart Road
Grantham
Lincolnshire
NG31 7NB

BGB (USA)

Call us today on +1 804 451 5211

1060 Port Walthall Drive
Colonial Heights
VA 23834
USA

www.bgbinnovation.com