



Specification sheet

Part No. A329A-T

4-58-10-25 SLIP RING
(Ag TOP TWO RINGS)

Print Date 16.10.23

Part No. A329A-T

4-58-10-25 SLIP RING (Ag TOP TWO RINGS)



Number of Rings 4

Outer Diameter (mm) 58

Max Amp Rating No Test Data Approx 30

Ring width (mm) 10

Bore (mm) 25

Min Voltage Spacing mm 7

Specifications

Part No. A329A-T

4-58-10-25 SLIP RING (Ag TOP TWO RINGS)



Material properties

Property	Value	Standard
RING MATERIAL	Bronze (PB1)	-
RISER MATERIAL	Brass (CZ121)	-
INSUALTION MATERIAL	DMC	-
HUB MATERIAL	N/A	-
RING PLATING MATERIAL	Silver **Top 2 rings only	-

RISERS properties

Property	Value	Standard
TYPE	Round	-
LENGTH (mm)	14mm	-
WIDTH (mm)	4mm	-
THICKNESS (mm)	4mm	-
RISER PLATING MATERIAL	N/A	-
NUMBER OF RISERS	5	-

TERMINALS properties

Property	Value	Standard
	N/A	-

Part No. A329A-T

4-58-10-25 SLIP RING (Ag TOP TWO RINGS)



GENERAL INFORMATION properties

Property	Value	Standard
OVERALL LENGTH (mm)	84mm	-
SECURING METHOD - THREAD SIZE	M5	-
SECURING METHOD - NUMBER OF HOLES	2	-
KEY WAY (Y/N)	N	-
NUMBER OF CHANNELS	4	-
BORE SIZE	25mm (H7)	-

ELECTRICAL INFORMATION properties

Property	Value	Standard
VOLTAGE RATING MAX	TBC (IEC)	-
CURRENT RATING MAX	30A	-



Part No. **A329A-T**

4-58-10-25 SLIP RING
(Ag TOP TWO RINGS)

BGB (UK)

Call us today on +44 (0) 1476 576280

Dysart Road
Grantham
Lincolnshire
NG31 7NB

BGB (USA)

Call us today on +1 804 451 5211

1060 Port Walthall Drive
Colonial Heights
VA 23834
USA

www.bgbinnovation.com