



Specification sheet

Part No. A342F

6-60-10-25 SLIPRING

Print Date 27.07.23

Part No. A342F

6-60-10-25 SLIPRING



Number of Rings 6

Outer Diameter (mm) 60

Max Amp Rating No Test Data Approx 45

Ring width (mm) 10

Bore (mm) 25

Min Voltage Spacing mm 6.5

Specifications

Part No. A342F

6-60-10-25 SLIPRING



Material properties

Property	Value	Standard
RING MATERIAL	BRONZE (PB1)	-
RISER MATERIAL	BRASS	-
INSUALTION MATERIAL	DMC	-
HUB MATERIAL	N/A	-
RING PLATING MATERIAL	N/A	-

RISERS properties

Property	Value	Standard
TYPE	M5 THREADED	-
LENGTH (mm)	12mm	-
WIDTH (mm)	N/A	-
THICKNESS (mm)	N/A	-
RISER PLATING MATERIAL	N/A	-
NUMBER OF RISERS	6	-

TERMINALS properties

Property	Value	Standard
	6.3 X 0.8 - 45 DEG M5	-
		-

Part No. A342F

6-60-10-25 SLIPRING



GENERAL INFORMATION properties

Property	Value	Standard
OVERALL LENGTH (mm)	121.5	-
SECURING METHOD - THREAD SIZE	M5	-
SECURING METHOD - NUMBER OF HOLES	3X M5 GRUB SCREWS	-
KEY WAY (Y/N)	N	-
NUMBER OF CHANNELS	6	-
BORE SIZE	Ø25 H7	-

ELECTRICAL INFORMATION properties

Property	Value	Standard
VOLTAGE RATING MAX	TBC (IEC)	-
CURRENT RATING MAX	45 AMPS	-



Part No. A342F

6-60-10-25 SLIPRING

BGB (UK)

Call us today on +44 (0) 1476 576280

Dysart Road
Grantham
Lincolnshire
NG31 7NB

BGB (USA)

Call us today on +1 804 451 5211

1060 Port Walthall Drive
Colonial Heights
VA 23834
USA

www.bgbinnovation.com